

Version Revision Date: MSDS Number: Date of last issue: -

1.0 02/12/2015 57113-00001 Date of first issue: 02/12/2015

#### **SECTION 1. IDENTIFICATION**

Product name : GOJO® ORIGINAL FORMULA™ Hand Cleaner

Manufacturer or supplier's details

Company name of supplier : GOJO Industries, Inc.

Address : One GOJO Plaza, Suite 500

Akron OH 44311

Telephone : 1 (330) 255-6000

Emergency telephone : 1-800-424-9300 CHEMTREC

Recommended use of the chemical and restrictions on use

Recommended use : Skin-care

Restrictions on use : This is a personal care or cosmetic product that is safe for

consumers and other users under normal and reasonably foreseeable use. Cosmetics and consumer products, specifically defined by regulations around the world, are exempt from the requirement of an SDS for the consumer. While this material is not considered hazardous, this SDS contains valuable information critical to the safe handling and proper use of the product for industrial workplace conditions as well as unusual and unintended exposures such as large spills. This SDS should be retained and available for employees and other users of this product. For specific

intended-use guidance, please refer to the information provided on the package or instruction sheet.

#### **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Serious eye damage : Category 1

**GHS Label element** 

Hazard pictograms :

Signal Word : Danger

Hazard Statements : H318 Causes serious eye damage.

Precautionary Statements : Prevention:

P280 Wear eye protection/ face protection.

Response:

### SAFETY DATA SHEET



# GOJO® ORIGINAL FORMULA™ Hand Cleaner

Version Revision Date: MSDS Number: Date of last issue: -

1.0 02/12/2015 57113-00001 Date of first issue: 02/12/2015

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER or doctor/ physician.

#### Other hazards

Repeated exposure may cause skin dryness or cracking.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

### Hazardous ingredients

Chemical Name	CAS-No.	Concentration (%)
Distillates (petroleum), hydrotreated light	64742-47-8	>= 30 - < 50
White mineral oil (petroleum)	8042-47-5	>= 10 - < 20
Ethoxylated branched C11-14, C13-rich alcohols	78330-21-9	>= 1 - < 5
Propylene glycol	57-55-6	>= 1 - < 5
Petrolatum	8009-03-8	>= 1 - < 5
Sodium Hydroxymethylglycinate	70161-44-3	>= 0.1 - < 1

#### **SECTION 4. FIRST AID MEASURES**

General advice : In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap as a precaution.

Get medical attention if symptoms occur.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention immediately.

If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

: Prolonged or repeated contact may dry skin and cause

irritation.

delayed

Causes serious eye damage.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment

when the potential for exposure exists.

Notes to physician : Treat symptomatically and supportively.



Version Revision Date: MSDS Number: Date of last issue: -

1.0 02/12/2015 57113-00001 Date of first issue: 02/12/2015

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Water spray

Alcohol-resistant foam

Dry chemical

Carbon dioxide (CO2)

Unsuitable extinguishing

media

: None known.

Specific hazards during fire

fighting

: Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

ucts

: Carbon oxides

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment

for fire-fighters

: In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Follow safe handling advice and personal protective

equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide diking or other appropriate

containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate

container.

Clean up remaining materials from spill with suitable

absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding



Version Revision Date: MSDS Number: Date of last issue: -

1.0 02/12/2015 57113-00001 Date of first issue: 02/12/2015

certain local or national requirements.

### **SECTION 7. HANDLING AND STORAGE**

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not get on skin or clothing.

Avoid inhalation of vapor or mist.

Do not swallow. Do not get in eyes.

Handle in accordance with good industrial hygiene and safety

practice.

Keep container tightly closed.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Keep tightly closed.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

# **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

### Ingredients with workplace control parameters

				•
Ingredients	CAS-No.	Value type	Control	Basis
		(Form of	parameters /	
		exposure)	Permissible	
			concentration	
Distillates (petroleum),	64742-47-8	TWA (Mist)	5 mg/m3	OSHA Z-1
hydrotreated light				
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
White mineral oil (petroleum)	8042-47-5	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhal-	5 mg/m3	ACGIH
		able fraction)		
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Propylene glycol	57-55-6	TWA	10 mg/m3	US WEEL
Petrolatum	8009-03-8	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhal-	5 mg/m3	ACGIH
		able fraction)		
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL

### Hazardous components without workplace control parameters

Ingredients	CAS-No.
Ingredients	CAS-NO.



Version Revision Date: MSDS Number: Date of last issue: -

1.0 02/12/2015 57113-00001 Date of first issue: 02/12/2015

Ethoxylated branched C11-14, C13-rich alcohols	78330-21-9
Sodium	70161-44-3
Hydroxymethylglycinate	

**Engineering measures** : Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

### Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided

by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled

release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Material : Impervious gloves

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before

breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:

Chemical resistant goggles must be worn.

If splashes are likely to occur, wear:

Face-shield

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Hygiene measures : Ensure that eye flushing systems and safety showers are

located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid



Version Revision Date: MSDS Number: Date of last issue: -

1.0 02/12/2015 57113-00001 Date of first issue: 02/12/2015

Color : opaque, white, yellow

Odor : solvent

Odor Threshold : No data available

pH : 9.0

Melting point/freezing point : No data available

Solidification / Setting point No data available

Initial boiling point and boiling

range

: No data available

Flash point : > 100 °C

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Density : 1 g/cm3

Solubility(ies)

Water solubility : soluble

Partition coefficient: n-

octanol/water

: Not applicable

Autoignition temperature : No data available

Decomposition temperature : The substance or mixture is not classified self-reactive.

Viscosity

Viscosity, kinematic : 10,000 - 45,000 mm2/s (20 °C)

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.



Version Revision Date: MSDS Number: Date of last issue: -

1.0 02/12/2015 57113-00001 Date of first issue: 02/12/2015

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

: Can react with strong oxidizing agents.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

: No hazardous decomposition products are known.

### **SECTION 11. TOXICOLOGICAL INFORMATION**

### Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

### **Acute toxicity**

Not classified based on available information.

**Product:** 

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

### **Ingredients:**

Distillates (petroleum), hydrotreated light:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.3 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute

inhalation toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

White mineral oil (petroleum):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity



Version Revision Date: MSDS Number: Date of last issue: -

1.0 02/12/2015 57113-00001 Date of first issue: 02/12/2015

Ethoxylated branched C11-14, C13-rich alcohols:

Acute oral toxicity : Acute toxicity estimate: 500 mg/kg

Method: Expert judgment

Propylene glycol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rabbit): > 159 mg/l, > 51091 ppm

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Petrolatum:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

Sodium Hydroxymethylglycinate:

Acute oral toxicity : LD50 (Rat): 1,050 mg/kg

Skin corrosion/irritation

Not classified based on available information.

**Product:** 

Result: No skin irritation

Ingredients:

Distillates (petroleum), hydrotreated light:

Assessment: Repeated exposure may cause skin dryness or cracking.

White mineral oil (petroleum):

Species: Rabbit

Result: No skin irritation

Ethoxylated branched C11-14, C13-rich alcohols:

Species: Rabbit

Result: No skin irritation

Remarks: Based on data from similar materials

Propylene glycol:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation



Version Revision Date: MSDS Number: Date of last issue: -

1.0 02/12/2015 57113-00001 Date of first issue: 02/12/2015

Petrolatum: Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Remarks: Based on data from similar materials

Sodium Hydroxymethylglycinate:

Species: Rabbit Result: Skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

**Ingredients:** 

Distillates (petroleum), hydrotreated light:

Species: Rabbit Result: No eye irritation

White mineral oil (petroleum):

Species: Rabbit

Result: No eye irritation

Ethoxylated branched C11-14, C13-rich alcohols:

Result: Irreversible effects on the eye

Remarks: Based on data from similar materials

Propylene glycol:

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

Petrolatum:

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

Remarks: Based on data from similar materials

Sodium Hydroxymethylglycinate:

Species: Rabbit

Result: Irritation to eyes, reversing within 21 days

Respiratory or skin sensitization

Skin sensitization: Not classified based on available information.

Respiratory sensitization: Not classified based on available information.

Product:

Assessment: Does not cause skin sensitization.

Ingredients:

Distillates (petroleum), hydrotreated light:

Test Type: Maximization Test (GPMT) Routes of exposure: Skin contact



Version Revision Date: MSDS Number: Date of last issue: -

1.0 02/12/2015 57113-00001 Date of first issue: 02/12/2015

Species: Guinea pig Result: negative

Remarks: Based on data from similar materials

White mineral oil (petroleum):

Test Type: Buehler Test

Routes of exposure: Skin contact

Species: Guinea pig Result: negative

Ethoxylated branched C11-14, C13-rich alcohols:

Test Type: Human repeat insult patch test (HRIPT)

Routes of exposure: Skin contact

Result: negative

Remarks: Based on data from similar materials

Propylene glycol:

Test Type: Maximization Test (GPMT) Routes of exposure: Skin contact

Species: Guinea pig Result: negative

Petrolatum:

Test Type: Buehler Test

Routes of exposure: Skin contact

Species: Guinea pig Result: negative

Remarks: Based on data from similar materials

Sodium Hydroxymethylglycinate:

Test Type: Maximization Test (GPMT) Routes of exposure: Skin contact

Species: Guinea pig Result: positive

Assessment: Probability or evidence of skin sensitization in humans

Germ cell mutagenicity

Not classified based on available information.

**Ingredients:** 

Distillates (petroleum), hydrotreated light:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Chromosomal aberration

Species: Rat

Application Route: Intraperitoneal injection

Result: negative

Remarks: Based on data from similar materials

White mineral oil (petroleum):

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Result: negative



Version Revision Date: MSDS Number: Date of last issue: -

1.0 02/12/2015 57113-00001 Date of first issue: 02/12/2015

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Propylene glycol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test

Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

Petrolatum:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Sodium Hydroxymethylglycinate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Unscheduled DNA synthesis (UDS) test with

mammalian liver cells in vivo

Species: Rat Result: negative

Carcinogenicity

Not classified based on available information.

**Ingredients:** 

White mineral oil (petroleum):

Species: Rat

Application Route: Ingestion Exposure time: 24 Months

Result: negative

Propylene glycol:

Species: Rat

Application Route: Ingestion Exposure time: 2 Years

Result: negative



Version Revision Date: MSDS Number: Date of last issue: -

1.0 02/12/2015 57113-00001 Date of first issue: 02/12/2015

Petrolatum: Species: Rat

Application Route: Ingestion Exposure time: 2 Years Result: negative

IARC No ingredient of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

**OSHA**No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential carcino-

gen by OSHA.

NTP No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Not classified based on available information.

**Ingredients:** 

Distillates (petroleum), hydrotreated light:

Effects on fertility : Test Type: One-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

Result: negative

White mineral oil (petroleum):

Effects on fertility : Test Type: One-generation reproduction toxicity study

Species: Rat

Application Route: Skin contact

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

Result: negative

Propylene glycol:

Effects on fertility : Species: Mouse

Application Route: Ingestion

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Mouse

Application Route: Ingestion

Result: negative



Version Revision Date: MSDS Number: Date of last issue: -

1.0 02/12/2015 57113-00001 Date of first issue: 02/12/2015

Petrolatum:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Skin contact

Result: negative

Remarks: Based on data from similar materials

Sodium Hydroxymethylglycinate:

Effects on fetal development : Species: Rat

Application Route: Ingestion

Result: negative

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

**Ingredients:** 

Distillates (petroleum), hydrotreated light:

Species: Rat NOAEL: > 10.4 mg/l

Application Route: inhalation (vapor)

Exposure time: 90 d

Remarks: Based on data from similar materials

White mineral oil (petroleum):

Species: Rat LOAEL: 160 mg/kg

Application Route: Ingestion

Exposure time: 90 d

Species: Rat LOAEL: >= 1 mg/l

Application Route: inhalation (dust/mist/fume)

Exposure time: 4 w

Method: OECD Test Guideline 412

Propylene glycol:

Species: Rat

NOAEL: 1,700 mg/kg Application Route: Ingestion

Exposure time: 2 y

Petrolatum: Species: Rat



Version Revision Date: MSDS Number: Date of last issue: -

1.0 02/12/2015 57113-00001 Date of first issue: 02/12/2015

NOAEL: 5,000 mg/kg Application Route: Ingestion

Exposure time: 2 y

### **Aspiration toxicity**

Not classified based on available information.

### **Product:**

No aspiration toxicity classification

### Ingredients:

# Distillates (petroleum), hydrotreated light:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

#### White mineral oil (petroleum):

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

### **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

### Ingredients:

# Distillates (petroleum), hydrotreated light:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 250 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Toxicity to daphnia and other

aquatic invertebrates

: EL50 (Acartia tonsa): > 3,193 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Toxicity to algae : EL50 (Skeletonema costatum (marine diatom)): > 3,200 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

NOELR (Skeletonema costatum (marine diatom)): 993 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

 NOELR (Ceriodaphnia dubia (water flea)): > 70 mg/l Exposure time: 8 d

Test substance: Water Accommodated Fraction

Toxicity to bacteria : EC50: > 100 mg/l

Exposure time: 3 h

# White mineral oil (petroleum):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h



Version Revision Date: MSDS Number: Date of last issue: -

1.0 02/12/2015 57113-00001 Date of first issue: 02/12/2015

Method: OECD Test Guideline 203

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae : NOEC (Pseudokirchneriella subcapitata (green algae)): 100

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic

toxicity)

: NOEC (Oncorhynchus mykiss (rainbow trout)): 1,000 mg/l

Exposure time: 28 d

Toxicity to daphnia and other aquatic invertebrates

(Chronic toxicity)

: NOEC (Daphnia magna (Water flea)): 1,000 mg/l

Exposure time: 21 d

Ethoxylated branched C11-14, C13-rich alcohols:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 5.6 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to daphnia and other

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l

Exposure time: 48 h

Remarks: Based on data from similar materials

Toxicity to algae : EC50: > 1 - 10 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to fish (Chronic

toxicity)

: NOEC (Lepomis macrochirus (Bluegill sunfish)): > 0.33 mg/l

Exposure time: 30 d

Remarks: Based on data from similar materials

Toxicity to daphnia and other

aquatic invertebrates

(Chronic toxicity)

: NOEC (Daphnia magna (Water flea)): 0.77 mg/l

Exposure time: 21 d

Remarks: Based on data from similar materials

Propylene glycol:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 40,613 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Ceriodaphnia dubia (water flea)): 18,340 mg/l

Exposure time: 48 h

Toxicity to algae : EC50 (Skeletonema costatum (marine diatom)): 19,000 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic

toxicity)

: Chronic Toxicity Value: 2,500 mg/l

Exposure time: 30 d

Toxicity to daphnia and other

aquatic invertebrates

: NOEC (Ceriodaphnia dubia (water flea)): 29,000 mg/l

Exposure time: 7 d



Version Revision Date: MSDS Number: Date of last issue: -

1.0 02/12/2015 57113-00001 Date of first issue: 02/12/2015

(Chronic toxicity)

Toxicity to bacteria : NOEC (Pseudomonas putida): > 20,000 mg/l

Exposure time: 18 h

Petrolatum:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >=

100 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other

aquatic invertebrates

(Chronic toxicity)

NOEC (Daphnia magna (Water flea)): 10 mg/l

Exposure time: 21 d

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

Sodium Hydroxymethylglycinate:

Toxicity to fish : LC50: > 10 - 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia pulex (Water flea)): > 10 - 100 mg/l

Exposure time: 48 h

Toxicity to algae : ErC50 (Desmodesmus subspicatus (Scenedesmus

subspicatus)): > 10 - 100 mg/l

Exposure time: 72 h

Toxicity to bacteria : EC50: > 100 mg/l

Exposure time: 120 h

Persistence and degradability

Ingredients:

Distillates (petroleum), hydrotreated light:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 82 % Exposure time: 24 d

Method: OECD Test Guideline 301F

White mineral oil (petroleum):

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 31 %



Version Revision Date: MSDS Number: Date of last issue: -

1.0 02/12/2015 57113-00001 Date of first issue: 02/12/2015

Exposure time: 28 d

Ethoxylated branched C11-14, C13-rich alcohols:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 95 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

Propylene glycol:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 98.3 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Petrolatum:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 31 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

Sodium Hydroxymethylglycinate:

Biodegradability : Result: Readily biodegradable.

Bioaccumulative potential

**Ingredients:** 

Propylene glycol:

Partition coefficient: n-

octanol/water

: log Pow: -1.07

**Sodium Hydroxymethylglycinate:** 

Partition coefficient: n-

octanol/water

: log Pow: < 3

Mobility in soil

No data available

Other adverse effects

No data available

## **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Dispose of as unused product.

Empty containers should be taken to an approved waste

handling site for recycling or disposal.

### SAFETY DATA SHEET



# GOJO® ORIGINAL FORMULA™ Hand Cleaner

Version Revision Date: MSDS Number: Date of last issue: -

1.0 02/12/2015 57113-00001 Date of first issue: 02/12/2015

### **SECTION 14. TRANSPORT INFORMATION**

### **International Regulation**

#### **UNRTDG**

Not regulated as a dangerous good

#### **IATA-DGR**

Not regulated as a dangerous good

#### **IMDG-Code**

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### **Domestic regulation**

#### **49 CFR**

Not regulated as a dangerous good

#### **SECTION 15. REGULATORY INFORMATION**

### **EPCRA - Emergency Planning and Community Right-to-Know**

#### **CERCLA Reportable Quantity**

Ingredients	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Sodium hydroxide	1310-73-2	1000	*

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Acute Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### **US State Regulations**

### Pennsylvania Right To Know

_		
Distillates (petroleum), hydrotreated light	64742-47-8	30 - 50 %
Water	7732-18-5	30 - 50 %
White mineral oil (petroleum)	8042-47-5	10 - 20 %
Oleic acid	112-80-1	5 - 10 %
Ethoxylated branched C11-14, C13-rich	78330-21-9	1 - 5 %
alcohols		
Propylene glycol	57-55-6	1 - 5 %



Version 1.0	Revision Date: 02/12/2015			)15	
	Petrolatur	n	8009-03-8	1 - 5 %	
	Sodium h	ydroxide	1310-73-2	0.1 - 1 %	
New	Jersey Right To Kno	DW .			
	Distillates	(petroleum), hydrotreated	d light 64742-47-8	30 - 50 %	
	Water		7732-18-5	30 - 50 %	
	White min	eral oil (petroleum)	8042-47-5	10 - 20 %	
	Oleic acid		112-80-1	5 - 10 %	
	Ethoxylate alcohols	ed branched C11-14, C13	3-rich 78330-21-9	1 - 5 %	
	Propylene	glycol	57-55-6	1 - 5 %	

California Prop 65 This product does not contain any chemicals known to the

State of California to cause cancer, birth, or any other

reproductive defects.

#### The ingredients of this product are reported in the following inventories:

AICS : All ingredients listed or exempt.


#### **Inventories**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), NECSI (Taiwan), TSCA (USA)

### **SECTION 16. OTHER INFORMATION**

### **Further information**

### NFPA:



Special hazard.

## HMIS III:

HEALTH	3
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, \* = Chronic

# Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)

ACGIH / TWA : 8-hour, time-weighted average



Version Revision Date: MSDS Number: Date of last issue: -

1.0 02/12/2015 57113-00001 Date of first issue: 02/12/2015

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA Z-1 / TWA : 8-hour time weighted average

US WEEL / TWA : 8-hr TWA

Sources of key data used to compile the Material Safety

Data Sheet

: Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 02/12/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8